


BANG

design: Roberto Mantovani



Supply current
Courant d'alimentation
Corriente de alimentación
500mA (V_i 2.9V)

Power
Puissance
Potencia
1.5W



CCT	Flux	CRI
2700K	128 lm	93
3000K	133 lm	93
3500K	143 lm	93
4000K	154 lm	93



Code Construction

Construction du code produit
Construcción del código de producto


BA | X | X | X | XX

BA	X	Shape Forma Forme	X	Emission Émission Emisión	X	Finishing Finitions Acabados	XX	Color Temp. Température couleur Temperatura de color
	1	Round Rond Redondo		1	Single Unique Único		1	White Blanc Blanco
	2	Square Carré Cuadrado		2	Double Doble		3	Chrome Cromo
							4	Gold Or Oro
							5	Black Noir Negro
							C	Custom Personnalisée Personalizado

Drivers (Remote)

Alimentateurs
Alimentadores

Series wiring
Câblage en série
Cableado en serie



For other driver options -
including Lutron, Dali and DMX -
please consult factory

Static White

500mA

Phase / 0-10V (Dual Dimming)

CCPRO10-A
Min. 1
Max. 6


CCPRO40-A
Min. 1
Max. 18

Optionals - Accessoires - Accesorios

CS1006

Recessing box

Boîtier d'encastrement
Caja de empotrar



CS1006.CPW

Concrete pour

Coulée de béton
Vertido de hormigón

