


BEAN


design: Roberto Mantovani

Supply current
 Courant d'alimentation
 Corriente de alimentación
500mA (V_f 2.9V)

Power
 Pouissance
 Potencia
1.5W



Photometric diagrams



CCT	Flux	CRI
2700K	128 lm	93
3000K	133 lm	93
3500K	143 lm	93
4000K	154 lm	93



Code Construction

Construction du code produit
 Construcción del código de producto

EA X XX X


EA	X	Shape Forma Forme	XX	Color Temp. Température couleur Temperatura de color	X	Finishing Finitions Acabados
		1 Round Rond Redondo		27 2700K 30 3000K 35 3500K 40 4000K		B White Blanc Blanco N Black Noir Negro K COR-TEN Z INOX AISI 316L Steel Acier Acero C Custom Personnalisée Personalizado

Drivers (Remote)

Alimentateurs
 Alimentadores

Series wiring

Câblage en série
 Cableado en serie



For other driver options -
 including Lutron, Dali and DMX -
 please consult factory


Static White	Phase / 0-10V (Dual Dimming)	
500mA	CCPRO10-A Min. 1 Max. 6	CCPRO40-A Min. 1 Max. 18

Optionals - Accessoires - Accesorios

CSLN01

Recessing box

Boîtier d'encastrement
 Caja de empotrar



CS1006.CPW

Concrete pour

Coulée de béton
 Vertido de hormigón

