


BUNGA

design: Roberto Mantovani

Supply current
 Courant d'alimentation
 Corriente de alimentación
500mA (V_f 2.9V)

Power
 Pouissance
 Potencia
1.5W



CCT	Flux	CRI
2700K	128 lm	90+
3000K	133 lm	90+
3500K	142 lm	90+
4000K	154 lm	85
Custom	TBD	

Code Construction

Construction du code produit
 Construcción del código de producto


JN1 | X | X | XX | 5 |

BG	X	Emission Émission Emisión	X	Finishing Finitions Acabados	XX	Color Temp. Température couleur Temperatura de color
	1	Single Unique Único		G	27	2700K
	2	Double Doble		N	30	3000K
				K	35	3500K
				Z	40	4000K
					CU	Custom

Optionals - Accessoires - Accesorios

Recessing box Boîtier d'encastrement Caja de empotrar

CSXT01



Note: cable cut to measure on request

Note: câble sur mesure disponible sur demande


Nota: cable a medida disponible a petición

Drivers

Alimentateurs
 Alimentadores

Series wiring

Câblage en série
 Cableado en serie



0-10V

FLEXA-60-PRO-CC-10V

Programmable 60W CC 0-10V Dimming
 Dimming Range: 0.01%

Min 1./Max. 18 Fixtures per Driver

Phase

FLEXA-12-500-CC-ELV

12W 500mA Constant Current
 Dimming Range: 10%

Min. 2/Max. 7 Fixtures per Driver

FLEXA-23-500-CC-ELV

23W 500mA Constant Current
 Dimming Range: 10%

Min 7./Max. 14 Fixtures per Driver

Lutron Forward Phase

LTEA.1

Hi-Lume Forward Phase
 20W 500mA Constant Current

Dimming Range: 1%
Min. 3/Max. 12 Fixtures per Driver

LTEA.2

Hi-Lume Forward Phase
 30W 500mA Constant Current

Dimming Range: 1%
Min. 12/Max. 18 Fixtures per Driver

Lutron Ecosystem

PEQ.1

Hi-Lume ECO System
 20W 500mA Constant Current

Dimming Range: 1%
Min. 3/Max. 12 Fixtures per Driver

PEQ.0

Hi-Lume ECO System Premier
 20W 500mA Constant Current

Dimming Range: 0.1%
Min. 3/Max. 12 Fixtures per Driver