


BUNGA

design: Roberto Mantovani

Supply current
Courant d'alimentation
Corriente de alimentación
500mA (V_i 2.9V)

Power
Pouissance
Potencia
1.5W



CCT	Flux	CRI
2700K	128 lm	93
3000K	133 lm	93
4000K	154 lm	93



Code Construction

Construction du code produit
Construcción del código de producto

BG | X | X | XX |


BG	X	Emission Émission Emisión	X	Finishing Finitions Acabados	XX	Color Temp. Température couleur Temperatura de color
	1	Single Unique Único		N	27	2700K
	2	Double Doble		K	30	3000K
				Z	40	4000K
				C	CU	Custom Personnalisée Personalizado

Drivers (Remote)

Alimentateurs
Alimentadores

Series wiring

Câblage en série
Cableado en serie



For other driver options -
including Lutron, Dali and DMX -
please consult factory


Static White	Phase / 0-10V (Dual Dimming)
500mA	CCPRO10-A Min. 1 Max. 6
	CCPRO40-A Min. 1 Max. 18

Note: cable cut to measure on request
Note: câble sur mesure disponible sur demande
Nota: cable a medida disponible a petición

Optionals - Accessoires - Accesorios

CSXT01

Recessing box
Boîtier d'encastrement
Caja de empotrar



CSXT01.CP

Concrete pour
Coulée de béton
Vertido de hormigón

