


GAGA

design: Lapo Grassellini



Supply current
 Courant d'alimentation
 Corriente de alimentación

500mA (V_i 2 x 18V)


Power
 Pouissance
 Potencia

2 x 10W



FLEXALIGHTING
 NORTH AMERICA

CCT	Flux _(x2)	CRI	CCT	Flux	CRI
2400K	837 lm	95+	Dim to Warm 1800K-3000K	725 lm	95
2700K	921 lm	98+	Tunable White 2700K-5000K	952 lm	95
3000K	977 lm	98+			
3500K	1016 lm	98+			
4000K	1055 lm	98+			



Code Construction

Construction du code produit
 Construcción del código de producto

GG1 X XX 9


GG1	X	Finishing Finitions Acabados	XX	Color Temp. Température couleur Temperatura de color	9
		1 White Blanc Blanco		24 2400K	
		5 Black Noir Negro		27 2700K	
		C Custom Personnalisée Personalizado		30 3000K	
				35 3500K	
				40 4000K	
				DW Dim Warm	
				TW Tunable White	
				CU Custom Personnalisée Personalizado	

Drivers (Remote)

Alimentateurs
 Alimentadores

Series wiring

Câblage en série
 Cableado en serie



For other driver options -
 including Lutron, Dali and DMX -
 please consult factory

Static White 500mA	Phase / 0-10V (Dual Dimming)
	CCPR040-A Min. 1 Max. 1
Dim to Warm 400mA	Phase / 0-10V (Dual Dimming)
	CCPR040-A Min. 1 Max. 1
Turnable White 500mA	Phase / 0-10V (Dual Dimming)
	Please consult manufactory for driver option

Optionals - Accessoires - Accesorios

DCVI.B.2

24VDC Constant Voltage to
 Constant Current Converter
 0-10V / Phase / Dim to Warm
 Compatible, 26W

