


JAN 2

design: Roberto Mantovani

Supply current
Courant d'alimentation
Corriente de alimentación
500mA (V_i 2.9V)

Power
Puissance
Potencia
1.5W



Photometric diagrams



CCT	Flux	CRI
2700K	128 lm	93
3000K	133 lm	93
3500K	143 lm	93
4000K	154 lm	93



Code Construction

Construction du code produit
Construcción del código de producto

JN1 | X | X | XX | 5


JN1	X	Shape Forma Forme	X	Finishing Finitions Acabados	XX	Color Temp. Température couleur Temperatura de color	5	Beam angle Angle de faisceau Ángulo del haz
		1 Round Rond Redondo		N Black Noir Negro		27 2700K		5 5°
		2 Square Carré Cuadrado		K COR-TEN		30 3000K		
				Z INOX AISI 316L Steel Acier Acero		35 3500K		
				C Custom Personnalisée Personalizado		40 4000K		
						CU Custom Personnalisée Personalizado		

Drivers (Remote)

Alimentateurs
Alimentadores

Series wiring

Câblage en série
Cableado en serie




For other driver options -
including Lutron, Dali and DMX -
please consult factory

Static White	Phase / 0-10V (Dual Dimming)
500mA	CCPR010-A Min. 1 Max. 6
	CCPR040-A Min. 1 Max. 18

Optionals - Accessoires - Accesorios


CSXT01

Recessing box
Boîtier d'encastrement
Caja de empotrar



CSXT01.CP

Concrete pour
Coulée de béton
Vertido de hormigón



Note: cable cut to measure on request
Note: câble sur mesure disponible sur demande
Nota: cable a medida disponible a petición