


KELLER S


design: Roberto Mantovani

Supply current
Courant d'alimentation
Corriente de alimentación
24VDC

Power
Puissance
Potencia
7.5W



Photometric diagrams



CCT	Flux	CRI
2400K	560 lm	95+
2700K	580 lm	98+
3000K	610 lm	98+
3500K	625 lm	98+
4000K	640 lm	98+



Code Construction

Construction du code produit
Construcción del código de producto

KE1 X XX 9 X


KE1	X	Finishing Finitions Acabados	XX	Color Temp. Température couleur Temperatura de color	9	X	Beam angle Angle de faisceau Ángulo del haz
		2 Aluminum Aluminium Aluminio		24 2400K		S 36°	
		5 Black Noir Negro		27 2700K		M 46°	
		6 Bronze Bronce		30 3000K		W 60°	
		C Custom Personnalisée Personalizado		35 3500K			
				40 4000K			
				CU Custom Personnalisée Personalizado			

Drivers (Remote)

Alimentateurs
Alimentadores

Parallel wiring

Câblage en parallèle
Cableado en paralelo



For other driver options -
including Lutron, Dali and DMX -
please consult factory

Static White

0-10V/Phase

DLM.100
Min. 1
Max. 12
DLM.60
Min. 1
Max. 7
DLM.30
Min. 1
Max. 3

L0D1

Low luminance louvre

Filtre basse luminance
Filtro de baja luminancia



Note: the filter must be ordered together with the lighting fixture
Note: le filtre doit être commandé en même temps que l'appareil
Nota: el filtro debe pedirse junto con la luminaria