


KING

design: Roberto Mantovani



Supply current
 Courant d'alimentation
 Corriente de alimentación

500mA (V_f 8.7V)

Power
 Pouissance
 Potencia

4.5W



CCT	Flux	CRI
2700K	540 lm	98+
3000K	600 lm	98+
3500K	610 lm	98+
4000K	620 lm	98+

Code Construction

Construction du code produit
 Construcción del código de producto

KGO|X|XX|

KGO	X	Finishing Finitions Acabados	XX	Color Temp. Température couleur Temperatura de color
		N Black Noir Negro		27 2700K
		K COR-TEN		30 3000K
				35 3500K
				40 4000K
		Z INOX AISI 316L Steel Acier Acero		CU Custom Personnalisée Personalizado
		C Custom Personnalisée Personalizado		


Note: cable cut to measure on request
Note: câble sur mesure disponible sur demande
Nota: cable a medida disponible a petición

Drivers (Remote)

Alimentateurs
 Alimentadores

Series wiring

Câblage en série
 Cableado en serie



For other driver options -
 including Lutron, Dali and DMX -
 please consult factory

Static White Phase / 0-10V (Dual Dimming)

500mA


CCPRO10-A
 Min. 1
 Max. 2

CCPRO40-A
 Min. 1
 Max. 6

Optionals - Accessoires - Accesorios


CSDS10

Recessing box
 Boîtier d'encastrement
 Caja de empotrar



CSDS10.CP

Concrete pour
 Coulée de béton
 Vertido de hormigón



DCVI.B.1

24VDC Constant Voltage to
 Constant Current Converter
 0-10V / Phase / Dim to Warm
 Compatible, 13W

