

LEONARD 36


design: Lapo Grassellini

Supply current
 Courant d'alimentation
 Corriente de alimentación
24VDC

Power
 Pouissance
 Potencia
4.5W


FLEXALIGHTING
 NORTH AMERICA

106mm (4.17")




Photometric diagrams


F002



F407



A113



CCT	Flux	CRI
2400K	472 lm	98+
2700K	421 lm	98+
3000K	446 lm	98+
3500K	464 lm	98+
4000K	482 lm	98+
Dim to Warm 1800K-3000K	416 lm	90



Code Construction

Construction du code produit
 Construcción del código de producto

LN36 XX 9 X


LN36	XX	Color Temp.	9	X	Beam angle
		Température couleur Temperatura de color			Angle de faisceau Ángulo del haz
		24 2400K		S	25°
		27 2700K		M	45°
		30 3000K		D	20+55° (Elliptical)
		35 3500K			
		40 4000K			
		DW Dim Warm			
		CU Custom Personnalisée Personalizado			

Drivers (Remote)

Alimentateurs
 Alimentadores

Parallel wiring

Câblage en parallèle
 Cableado en paralelo



Static White/DW 0-10V/Phase

CV2496A
 Min. 1
 Max. 20

L001

Low luminance louver
 Filtre basse luminance
 Filtro de baja luminancia



Note: the filter must be ordered together with the lighting fixture
Note: le filtre doit être commandé en même temps que l'appareil
Nota: el filtro debe pedirse junto con la luminaria