


MAL 10

design: Lapo Grassellini



Supply current
 Courant d'alimentation
 Corriente de alimentación
500mA (V_f 18V)

Power
 Pouissance
 Potencia
10W




FLEXALIGHTING

NORTH AMERICA

Photometric diagrams

F975



WALL WASHER

CCT	Flux	CRI	CCT	Flux	CRI
2400K	837 lm	95+	Dim to Warm	725 lm	95
2700K	921 lm	98+	1800K-3000K		
3000K	977 lm	98+			
3500K	1016 lm	98+			
4000K	1055 lm	98+			



Code Construction

Construction du code produit
 Construcción del código de producto

MA1|XX|9|X|


MA1	XX	Color Temp. Température couleur Temperatura de color	9	Beam angle Angle de faisceau Ángulo del haz	X	Finishing Finitions Acabados
		24 2400K		9 Wall Washer		N Black Noir Negro
		27 2700K				K COR-TEN
		30 3000K				Z INOX AISI 316L
		35 3500K				Steel Acier
		40 4000K				Acero
		DW Dim Warm				C Custom Personnalisée Personalizado
		CU Custom Personnalisée Personalizado				

Drivers (Remote)

Alimentateurs
 Alimentadores

Series wiring

Câblage en série
 Cableado en serie



For other driver options -
 including Lutron, Dali and DMX -
 please consult factory

Static White	Phase / 0-10V (Dual Dimming)
500mA	CCPRO10-A Min. 1 Max. 1
	CCPRO40-A Min. 1 Max. 3
Dim to Warm	Phase / 0-10V (Dual Dimming)
400mA	CCPRO10-A Min. 1 Max. 1
	CCPRO40-A Min. 1 Max. 3

Optionals - Accessoires - Accesorios

Note: cable cut to measure on request


Note: câble sur mesure disponible sur demande

Nota: cable a medida disponible a petición

CSDS20

Recessing box


Boîtier d'encastrement
 Caja de empotrar



CSDS20.CP

Concrete pour

Coulée de béton
 Vertido de hormigón



DCVI.B.1

24VDC Constant Voltage to
 Constant Current Converter
 0-10V / Phase / Dim to Warm
 Compatible, 13W

