


MAL 20

design: Lapo Grassellini




Supply current
 Courant d'alimentation
 Corriente de alimentación
500mA (V_f 36V)

Power
 Pouissance
 Potencia
20W



Photometric diagrams



CCT	Flux	CRI
2700K	1659 lm	93
3000K	1752 lm	93
3500K	1873 lm	93
4000K	1925 lm	93



Code Construction

Construction du code produit
 Construcción del código de producto

MA2 XX 9 X

MA2	XX	Color Temp. Température couleur Temperatura de color	9	Beam angle Angle de faisceau Ángulo del haz	X	Finishing Finitions Acabados
		27 2700K 30 3000K 35 3500K 40 4000K CU Custom Personnalisée Personalizado		9 Wall Washer		N Black Noir Negro K COR-TEN Z INOX AISI 316L Steel Acier Acero C Custom Personnalisée Personalizado


Note: cable cut to measure on request
Note: câble sur mesure disponible sur demande
Nota: cable a medida disponible a petición

Drivers (Remote)

Alimentateurs
 Alimentadores

Series wiring

Câblage en série
 Cableado en serie



For other driver options -
 including Lutron, Dali and DMX -
 please consult factory

Static White Phase / 0-10V (Dual Dimming)


500mA

CCPRO40-A
 Min. 1
 Max. 1

Optionals - Accessoires - Accesorios


CSDS20

Recessing box
 Boîtier d'encastrement
 Caja de empotrar



CSDS20.CP

Concrete pour
 Coulée de béton
 Vertido de hormigón



DCVI.B.2

24VDC Constant Voltage to
 Constant Current Converter
 0-10V / Phase / Dim to Warm
 Compatible, 26W

