


MARUPE 12

design: Roberto Mantovani



Supply current
Courant d'alimentation
Corriente de alimentación


Power
Pouissance
Potencia

500mA (V_f 8.7V) (CC)
500mA (V_f 2x8.7V) (CC)

4.5W (single)
9W (double)



Photometric diagrams



CCT	Flux	CRI	CCT	Flux	CRI
2400K	472 lm	95+	Dim to Warm	416 lm	90
2700K	421 lm	98+	1800K-3000K		
3000K	446 lm	98+			
3500K	464 lm	98+			
4000K	482 lm	98+			



Code Construction

Construction du code produit
Construcción del código de producto

MW | X | 2 | X | X | X | XX | CC | E


MW	X	Emission Émission Emisión	2	X	Finishing Finitions Acabados	X	Beam angle Angle de faisceau Ángulo del haz	X	Beam angle Angle de faisceau Ángulo del haz	XX	Color Temp. Température couleur Temperatura de color	CC	E
		1 Single Unique Único			1 White Blanc Blanco		1 25°		1 25°		24 2400K		
		2 Double Doble			5 Black Noir Negro		2 45°		2 45°		27 2700K		
					C Custom Personnalisée Personalizado		D Blind Borgne Ciego		D Blind Borgne Ciego		30 3000K		
											35 3500K		
											40 4000K		
											DW Dim Warm		
											CU Custom Personnalisée Personalizado		

Drivers (Remote)

Alimentateurs
Alimentadores

Series wiring

Câblage en série
Cableado en serie



For other driver options -
including Lutron, Dali and DMX -
please consult factory

Static White	Phase / 0-10V (Dual Dimming)
500mA 4.5W	CCPR010-A Min. 1 Max. 2
	CCPR040-A Min. 1 Max. 6
Dim to Warm	Phase / 0-10V (Dual Dimming)
250mA 4.5W	CCPR010-A Min. 1 Max. 2
	FCCPR040-A Min. 1 Max. 3

Static White	Phase / 0-10V (Dual Dimming)
500mA 9W	CCPR010-A Min. 1 Max. 1
	CCPR040-A Min. 1 Max. 3
Dim to Warm	Phase / 0-10V (Dual Dimming)
400mA 9W	CCPR010-A Min. 1 Max. 1
	CCPR040-A Min. 1 Max. 3

Optionals - Accessoires - Accesorios

DCVI.B.1

24VDC Constant Voltage to
Constant Current Converter
0-10V / Phase / Dim to Warm
Compatible, 13W

