


MINIAIR

design: Roberto Mantovani



Supply current
Courant d'alimentation
Corriente de alimentación
500mA (V, 2.9V)

Power
Puissance
Potencia
1.5W



CCT	Flux	CRI
2700K	128 lm	93
3000K	133 lm	93
4000K	154 lm	93



Code Construction

Construction du code produit
Construcción del código de producto

MXR | X | X | XX


MXR	X	Emission Émission Emisión	X	Finishing Finitions Acabados	XX	Color Temp. Température couleur Temperatura de color
	1	Single Unique Único		N	Black Noir Negro	27 2700K
	2	Double Doble		K	COR-TEN	30 3000K
				Z	INOX AISI 316L Steel Acier Acero	40 4000K
				C	Custom Personnalisée Personalizado	CU Custom Personnalisée Personalizado

Drivers (Remote)

Alimentateurs
Alimentadores

Series wiring

Câblage en série
Cableado en serie



For other driver options -
including Lutron, Dali and DMX -
please consult factory

Static White

500mA

Phase / 0-10V (Dual Dimming)

CCPRO10-A
Min. 1
Max. 6

CCPRO40-A
Min. 1
Max. 18

Note: cable cut to measure on request

Note: câble sur mesure disponible sur demande


Nota: cable a medida disponible a petición

Optionals - Accessoires - Accesorios

CSXT01

Recessing box

Boîtier d'encastrement
Caja de empotrar



CSXT01.CP

Concrete pour

Coulée de béton
Vertido de hormigón

