


MINISASHA 110 DISPLAY

design: Lapo Grassellini




Supply current
Courant d'alimentation
Corriente de alimentación
350mA (V_i 8.7V)

Power
Pouissance
Potencia
3W



Photometric diagrams



CCT	Flux	CRI
2700K	267 lm	98+
3000K	279 lm	98+
3500K	292 lm	98+
4000K	309 lm	98+



Code Construction

Construction du code produit
Construcción del código de producto

MSD11 | X | X | XX |


MSD11	X	Finishing Finitions Acabados	X	Beam angle Angle de faisceau Ángulo del haz	XX	Color Temp. Température couleur Temperatura de color
	1	White Blanc Blanco	1	18°	27	2700K
	5	Black Noir Negro	2	40°	30	3000K
	C	Custom Personnalisée Personalizado			35	3500K
					42	4200K
					CU	Custom Personnalisée Personalizado

Drivers (Remote)

Alimentateurs
Alimentadores

Series wiring

Câblage en série
Cableado en serie



For other driver options -
including Lutron, Dali and DMX -
please consult factory

Static White	Phase / 0-10V (Dual Dimming)
350mA	CCPRO10-A Min. 1 Max. 3 CCPRO40-A Min. 1 Max. 6

DCVI.B.1

24VDC Constant Voltage to
Constant Current Converter
0-10V / Phase / Dim to Warm
Compatible, 13W

