


NAP 10

design: Lapo Grassellini




Supply current
 Courant d'alimentation
 Corriente de alimentación
500mA (V_i 18V)

Power
 Pouissance
 Potencia
10W



Photometric diagrams



CCT	Flux	CRI	CCT	Flux	CRI
2400K	837 lm	95+	Dim to Warm 1800K-3000K	725 lm	95
2700K	921 lm	98+	Tunable White 2700K-5000K	952 lm	95
3000K	977 lm	98+			
3500K	1016 lm	98+			
4000K	1055 lm	98+			



Code Construction

Construction du code produit
 Construcción del código de producto

NA1 | X | XX | 9 |


NA1	X	Finishing Finitions Acabados	XX	Color Temp. Température couleur Temperatura de color	9	Beam angle Angle de faisceau Ángulo del haz
		1 White Blanc Blanco		24 2400K		9 Wall Washer
		5 Black Noir Negro		27 2700K		
		C Custom Personnalisée Personalizado		30 3000K		
				35 3500K		
				40 4000K		
				DW Dim Warm		
				TW Tunable White		
				CU Custom Personnalisée Personalizado		

Drivers (Remote)

Alimentateurs
 Alimentadores

Series wiring


Câblage en série
 Cableado en serie



For other driver options -
 including Lutron, Dali and DMX -
 please consult factory


Static White 500mA	Phase / 0-10V (Dual Dimming)
	CCPR010-A Min. 1 Max. 1
	CCPR040-A Min. 1 Max. 3
Dim to Warm 400mA	Phase / 0-10V (Dual Dimming)
	CCPR010-A Min. 1 Max. 1
	CCPR040-A Min. 1 Max. 3
Turnable White 500mA	Please consult factory for driver options

MP-R065
 Mounting Plate
 with 65mm Hole



T-Bar Installation


R01065
 Mounting Plate
 with 65mm Hole



IC Housings

IC064R01065
 Recessed Box for
 Insulated Ceiling
 with 65mm Hole

AT064R01065
 Air Tight Recessed
 Box for Insulated
 Ceiling with
 65mm Hole



Optionals - Accessoires - Accesorios

DCVI.B.1
 24VDC Constant Voltage to
 Constant Current Converter
 0-10V / Phase / Dim to Warm
 Compatible, 13W

