


NAP 20


design: Lapo Grassellini

Supply current
Courant d'alimentation
Corriente de alimentación
500mA (V_f 36V)

Power
Puissance
Potencia
20W



Photometric diagrams



CCT	Flux	CRI
2700K	1659 lm	93
3000K	1752 lm	93
3500K	1873 lm	93
4000K	1925 lm	93

Code Construction

Construction du code produit
Construcción del código de producto

NA2 X XX 9


NA2	X	Finishing Finitions Acabados	XX	Color Temp. Température couleur Temperatura de color	9	Beam angle Angle de faisceau Ángulo del haz
		1 White Blanc Blanco		27 2700K		9 Wall Washer
		5 Black Noir Negro		30 3000K		
		C Custom Personnalisée Personalizado		35 3500K		
				40 4000K		
				CU Custom Personnalisée Personalizado		

Drivers (Remote)

Alimentateurs
Alimentadores

Series wiring

Câblage en série
Cableado en serie




For other driver options -
including Lutron, Dali and DMX -
please consult factory

Static White Phase / 0-10V (Dual Dimming)

500mA


CCPR040-A
Min. 1
Max. 1

MP-R065
Mounting Plate
with 65mm Hole



T-Bar Installation


R02065
Mounting Plate
with 65mm Hole



IC Housings

IC086R02065
Recessed Box for
Insulated Ceiling
with 65mm Hole

AT086R02065
Air Tight Recessed
Box for Insulated
Ceiling with
65mm Hole



Optionals - Accessoires - Accesorios

DCVI.B.2

24VDC Constant Voltage to
Constant Current Converter
0-10V / Phase / Dim to Warm
Compatible, 26W

