


NONE Q10


design: Roberto Mantovani

Supply current
Courant d'alimentation
Corriente de alimentación
500mA (V_I 18V)

Power
Puissance
Potencia
10W



Photometric diagrams




CCT	Flux	CRI
2700K	860 lm	98+
3000K	912 lm	98+
3500K	949 lm	98+
4000K	985 lm	85
† Dim Warm 1800K-3000K	725 lm	95

Code Construction

Construction du code produit
Construcción del código de producto


NQW | X | XX | 9 | 1

NQW	X	Finishing Finitions Acabados	XX	Color Temp. Température couleur Temperatura de color	9	1
	1	White Blanc Blanco	27	2700K		
	5	Black Noir Negro	30	3000K		
			35	3500K		
			40	4000K		
			DW	Dim Warm † @ 420mA		




Q02080-W0A
Mounting Plate
with 80mm Hole

A - 203.2mm (8")
B - 203.2mm (8")
C - 80mm (3.15")
x 80mm (3.15")



Q02080
Mounting Plate
with 80mm Hole

A - 203.2mm (8")
B - 203.2mm (8")
C - 80mm (3.15")
x 80mm (3.15")



IC086Q02080
Recessed Box for Insulated Ceiling
with 80mm Hole


AT086Q02080
Air Tight Recessed Box for Insulated
Ceiling with 80mm Hole

Drivers

Alimentateurs
Alimentadores

Series wiring

Câblage en série
Cableado en serie



0-10V

FLEXA-60-PRO-CC-10V

Programmable 60W CC 0-10V Dimming
Dimming Range: 0.01%

Min 1./Max. 3 Fixtures per Driver

Phase

FLEXA-12-500-CC-ELV

12W 500mA Constant Current
Dimming Range: 10%

Min. 1/Max. 1 Fixtures per Driver

FLEXA-23-500-CC-ELV

23W 500mA Constant Current
Dimming Range: 10%

Min 1./Max. 2 Fixtures per Driver

Lutron Forward Phase

LTEA.1

Hi-Lume Forward Phase
20W 500mA Constant Current
Dimming Range: 1%

Min. 1/Max. 2 Fixtures per Driver

LTEA.2

Hi-Lume Forward Phase
30W 500mA Constant Current
Dimming Range: 1%

Min. 2/Max. 3 Fixtures per Driver

Lutron Ecosystem

PEQ.1

Hi-Lume ECO System
20W 500mA Constant Current
Dimming Range: 1%

Min. 1/Max. 2 Fixtures per Driver

PEQ.0


Hi-Lume ECO System Premier
20W 500mA Constant Current
Dimming Range: 0.1%

Min. 1/Max. 2 Fixtures per Driver

Optionals - Accessoires - Accesorios

Plasterboard recessing frame

Boîtier d'encastrement pour plaques de plâtre
Cajetín para placas de yeso



ZQC004

White
Blanc
Blanco

ZQC004B

Black
Noir
Negro