



OLU 6

design: Roberto Mantovani




Supply current
Courant d'alimentation
Corriente de alimentación
500mA (V_f 8.7V)

Power
Puissance
Potencia
4.5W



Photometric diagrams



CCT	Flux	CRI
2700K	128 lm	98+
3000K	133 lm	98+
3500K	142 lm	98+
4000K	154 lm	85
Custom	TBD	

Code Construction

Construction du code produit
Construcción del código de producto

LU2 | X | XX | X | E


LU2	X	Finishing Finitions Acabados	XX	Color Temp. Température couleur Temperatura de color	X	Beam angle Angle de faisceau Ángulo del haz	E
		2 Aluminum Aluminium Aluminio		27 2700K		S 25°	
		5 Black Noir Negro		30 3000K		F 60°	
		6 Bronze Bronze		35 3500K			
				40 4000K			
				CU Custom			

Optionals

Accessori - Accessoires
Zubehör - Accesorios

XP0022

Earth spike
Piquet de terre
Pico de la tierra




Note: cable cut to measure on request
Note: câble sur mesure disponible sur demande
Nota: cable a medida disponible a petición

Drivers

Alimentateurs
Alimentadores

Series wiring

Câblage en série
Cableado en serie



0-10V

FLEXA-60-PRO-CC-10V

Programmable 60W CC 0-10V Dimming
Dimming Range: 0.01%
Min 1./Max. 6 Fixtures per Driver

Phase

FLEXA-12-500-CC-ELV

12W 500mA Constant Current
Dimming Range: 10%
Min. 1/Max. 2 Fixtures per Driver

FLEXA-23-500-CC-ELV

23W 500mA Constant Current
Dimming Range: 10%
Min 3./Max. 5 Fixtures per Driver

Lutron Forward Phase

LTEA.1

Hi-Lume Forward Phase
20W 500mA Constant Current
Dimming Range: 1%
Min. 2/Max. 4 Fixtures per Driver

LTEA.2

Hi-Lume Forward Phase
30W 500mA Constant Current
Dimming Range: 1%
Min. 4/Max. 6 Fixtures per Driver

Lutron Ecosystem

PEQ.1

Hi-Lume ECO System
20W 500mA Constant Current
Dimming Range: 1%
Min. 2/Max. 4 Fixtures per Driver

PEQ.0

Hi-Lume ECO System Premier
20W 500mA Constant Current
Dimming Range: 0.1%
Min. 2/Max. 4 Fixtures per Driver