


TASK 2

design: Roberto Mantovani


Supply current
 Courant d'alimentation
 Corriente de alimentación
500mA (V_f 2.9V)

Power
 Pouissance
 Potencia
1.5W

FLEXALIGHTING
 NORTH AMERICA



Photometric diagrams



CCT	Flux	CRI
2700K	128 lm	93
3000K	133 lm	93
3500K	143 lm	93
4000K	154 lm	93

Code Construction

Construction du code produit
 Construcción del código de producto

TS | X | XX | 5 |


TS	X	Finishing	XX	Color Temp.	5	Beam angle
		Finitions Acabados		Température couleur Temperatura de color		Angle de faisceau Ángulo del haz
	1	White Blanc Blanco	27	2700K	5	5°
	5	Black Noir Negro	30	3000K		
			35	3500K		
			40	4000K		
	C	Custom Personnalisée Personalizado	CU	Custom Personnalisée Personalizado		

Drivers (Remote)

Alimentateurs
 Alimentadores

Series wiring

Câblage en série
 Cableado en serie




For other driver options -
 including Lutron, Dali and DMX -
 please consult factory

Static White	Phase / 0-10V (Dual Dimming)
500mA	CCPRO10-A Min. 1 Max. 6 CCPRO40-A Min. 1 Max. 18

MP-R030


Mounting Plate
 with 30mm Hole



T-Bar Installation

R01030

Mounting Plate
 with 30mm Hole



IC Housings

IC064R01030

Recessed Box for
 Insulated Ceiling
 with 30mm Hole

AT064R01030

Air Tight Recessed
 Box for Insulated
 Ceiling with
 30mm Hole

