



UMA

design: Roberto Mantovani



Photometric diagrams



Supply current
Courant d'alimentation
Corriente de alimentación
350mA (V, 2.9V)

Power
Pouissance
Potencia
1W



CCT	Flux	CRI
2700K	81 lm	93
3000K	81 lm	93
3500K	100 lm	93
4000K	107 lm	93



Code Construction

Construction du code produit
Construcción del código de producto

UM X X 2 XX


UM	X	Shape Forma Forme	X	Finishing Finitions Acabados	2	XX	Color Temp. Température couleur Temperatura de color
		1 Round Rond Redondo		1 White Blanc Blanco			27 2700K
		2 Square Carré Cuadrado		3 Chrome Cromo			30 3000K
				4 Gold Or Oro			35 3500K
				5 Black Noir Negro			40 4000K
				6 Bronze Bronce			CU Custom Personnalisée Personalizado
				C Custom Personnalisée Personalizado			

Drivers (Remote)

Alimentateurs
Alimentadores

Series wiring

Câblage en série
Cableado en serie



For other driver options -
including Lutron, Dali and DMX -
please consult factory

Static White

350mA

Phase / 0-10V (Dual Dimming)

CCPR010-A
Min. 1
Max. 9

CCPR040-A
Min. 1
Max. 18

Optionals - Accessoires - Accesorios

CS1005

Recessing box

Boîtier d'encastrement
Caja de empotrar

