


ZERO R6


design: Roberto Mantovani

Supply current
Courant d'alimentation
Corriente de alimentación
500mA (V_f 8.7V)

Power
Puissance
Potencia
4.5W



Photometric diagrams



CCT	Flux	CRI	CCT	Flux	CRI
2400K	472 lm	95+	Dim to Warm	416 lm	90
2700K	421 lm	98+	1800K-3000K		
3000K	446 lm	98+			
3500K	464 lm	98+			
4000K	482 lm	98+			

Code Construction

Construction du code produit
Construcción del código de producto

ZW1 | X | X | XX | E


ZW1	X	Finishing	X	Beam angle	XX	Color Temp.	E
		Finitions Acabados		Angle de faisceau Ángulo del haz		Température couleur Temperatura de color	
	1	White Blanc Blanco	1	25°	24	2400K	
	5	Black Noir Negro	2	45°	27	2700K	
	C	Custom Personnalisée Personalizado			30	3000K	
					35	3500K	
					40	4000K	
					DW	Dim Warm	
					CU	Custom Personnalisée Personalizado	

Drivers (Remote)

Alimentateurs
Alimentadores

Series wiring

Câblage en série
Cableado en serie



For other driver options -
including Lutron, Dali and DMX -
please consult factory

Static White	Phase / 0-10V (Dual Dimming)
500mA	CCPR010-A Min. 1 Max. 2
	CCPR040-A Min. 1 Max. 6
Dim to Warm	Phase / 0-10V (Dual Dimming)
250mA	CCPR010-A Min. 1 Max. 2
	CCPR040-A Min. 1 Max. 3


L001

Low luminance louvre
Filtre basse luminance
Filtro de baja luminancia




Note: the filter must be ordered together with the lighting fixture
Note: le filtre doit être commandé en même temps que l'appareil
Nota: el filtro debe pedirse junto con la luminaria

MP-R045
Mounting Plate
with 45mm Hole



T-Bar Installation


R01045
Mounting Plate
with 45mm Hole



IC Housings

IC064R01045
Recessed Box for
Insulated Ceiling
with 45mm Hole


AT064R01045
Air Tight Recessed
Box for Insulated
Ceiling with
45mm Hole



Accessories - Accessoires - Accesorios

ZQC001


**Plasterboard
recessing frame**
Boîtier d'encastrement
pour plaques de plâtre
Cajetín para placas de yeso



Hole Cut:
45mm
(1.77")

ZQC001.BMK

Backmount frame
Pierre/bois montage arrière
Roca/madera montaje trasero



Hole Cut:
34mm
(1.34")

Optionals - Accessoires - Accesorios

DCVI.B.1

24VDC Constant Voltage to
Constant Current Converter
0-10V / Phase / Dim to Warm
Compatible, 13W

