




IP RATED PROJECTORS

ZOOM 10

design: Lapo Grassellini



Supply current
Courant d'alimentation
Corriente de alimentación
500mA (V_f 18V)

Power
Pouissance
Potencia
10W



FLEXALIGHTING

NORTH AMERICA



Adjustable optics

Optique réglable
Óptica ajustable

10-55°

CCT	Flux	CRI
2400K	837 lm	95+
2700K	921 lm	98+
3000K	977 lm	98+
3500K	1016 lm	98+
4000K	1055 lm	98+

Code Construction

Construction du code produit
Construcción del código de producto

ZM2 | X | XX


ZM2	X	Finishing Finitions Acabados	XX	Color Temp. Température couleur Temperatura de color	Adjustable optics Optique réglable Óptica ajustable
		2 Aluminum Aluminium Aluminio		24 2400K	
		5 Black Noir Negro		27 2700K	
		6 Bronze Bronze		30 3000K	
		C Custom Personnalisée Personalizado		35 3500K	
				40 4000K	
				CU Custom Personnalisée Personalizado	10-55°

Drivers (Remote)

Alimentateurs
Alimentadores

Series wiring

Câblage en série
Cableado en serie




For other driver options -
including Lutron, Dali and DMX -
please consult factory

Static White	Phase / 0-10V (Dual Dimming)	
500mA	CCPR010-A Min. 1 Max. 1	CCPR040-A Min. 1 Max. 3

Optionals - Accessoires - Accesorios

CP0022

Earth spike
Piquet de terre
Pico de la tierra



DCVI.B.1

24VDC Constant Voltage to
Constant Current Converter
0-10V / Phase / Dim to Warm
Compatible, 13W

